

40- Safety Data Sheet

Aerosol Low Irritant Surface Spray

COMPANY AND PRODUCT IDENTIFICATION

Company Name Aaron Laboratories Pty Ltd
ABN 060 004 856 848
Address 21 Kitchen Road, Dandenong, VIC, 3175
Emergency Tel: (+614) 1817 9157
 (+614) 0730 0286
Tel / Fax: (+613) 9706 7673 / (+613) 9706 7622
Email: joseph@aaronlab.com.au

Product Name Astro Aerosol Residual Insecticide 330g
Other Names Not relevant
Manufacturers Code ENVU 001
Recommended use Residual insecticide

Poisons Information Centre

AUSTRALIA 13 11 26
NEW ZEALAND 0800 764 766 or 0800 POISON

HAZARD(S) IDENTIFICATION

Hazard Classification This product is classified as hazardous under Australian WHS Regulations. This product is classified as a Dangerous Good by the Australian Dangerous Goods Code.

Aerosols, Cat 1
 Sensitisation of Skin, Cat 1
 Aspiration Hazard, Cat 1

Hazard Statement(s) Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.
 H222 Extremely flammable aerosol.
 H280 Contain gas under pressure; may explode if heated.
 H317 May cause an allergic skin reaction.
 H304 May be fatal if swallowed and enters the airways.

Signal Danger

Hazard Symbol



Precautionary Statement(s) P101 If medical advice is needed, have product container or label at hand.

40- Safety Data Sheet

Aerosol Low Irritant Surface Spray

P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. -No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/fumes/gas/mist/vapours/spray.
P271 Use only in a well-ventilated area.
P312 Call a POISON CENTER/ doctor if you feel unwell
P305 IF IN EYES: hold eyes open, flood with water for at least 15 minutes and see a doctor.
P302 IF ON SKIN: wash thoroughly.
P301 + P331 IF SWALLOWED, rinse mouth with water. DO NOT induce vomiting.
P402 Store in a cool dry place.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

For further health and safety information please refer to the full SDS.

Note: This product should not be used in any purpose or manner contrary to recommended use unless authorised.

COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Proportion
Permethrin	52645-53-1	<2%
Naptha petroleum hydrotreated heavy	64742-48-9	10-30%
Hydrocarbon propellant		60-90%
- Propane	74-98-6	
- Butane	106-97-8	
Other ingredients		to 100%

FIRST AID MEASURES

For advice, contact a Poisons Information Centre 131126. Ensure medical personnel are aware of the identity and nature (hydrocarbon propelled aerosol) involved.

Inhalation: Remove victim to fresh air to prevent further exposure. Propane is an asphyxiant. If breathing difficulties are experienced, seek immediate medical care. Do not use direct mouth to mouth method of resuscitation, use alternative respiratory method.

Skin Contact: Remove contaminated clothing and shoes and wash well skin with warm soapy water. If irritation persists, contact a doctor

Eye Contact: Flush out immediately with running water for at least 15 minutes. If symptoms persist, seek medical attention.

40- Safety Data Sheet

Aerosol Low Irritant Surface Spray

Ingestion: Due to high volatility of product, this is not likely to occur. If sprayed in mouth, rinse mouth with plenty of water. If swallowed, do NOT induce vomiting. Seek medical attention.

FIRE FIGHTING MEASURES

Beware- heat greater than 50 C / 122 °F may cause these extremely flammable, pressurised dispensers to rupture, and violently rocket in various directions. These rockets will release flammable and potentially toxic gasses, which will increase the risk of fire spreading. In extinguishing any fire beware of any residual unburnt gas that could reignite.

Suitable Extinguishing Media Small fire: Use water spray/fog/foam, dry chemical or carbon dioxide (CO₂).
Large fire: Use water spray/fog/foam.

Hazards Aerosols may rupture and rocket (become projectiles) when exposed to excessive heat. Released gases can form extremely flammable, invisible, odourless explosive mixtures with air. Released gases can be heavier than air and travel to source of ignition causing flashback. Hazardous concentrations can accumulate in a confined space (pits, low laying areas). Fire can produce irritating, poisonous and corrosive gases. High concentration of gas could cause dizziness or asphyxiation without warning

Precautions / PPE For large quantities, consider initial evacuation for at least 100m in all directions.
Fight fire from protected position or use unmanned hose holders or monitor nozzles.
Use spark-proof tools and explosion-proof equipment.
Wear SCBA and protective gloves. Structural firefighter's uniform provides limited protection. If large amounts are involved, wear SCBA and chemical splash suit.
If impossible to safely extinguish fire, protect surroundings, withdraw from area and allow fire to burn.

Hazchem Code (for Placarding and transport only) If safe to do so, move undamaged aerosols from fire area but do not approach hot aerosols.
Cool aerosols with water before handling.
2YE
Class 2 flammable Gas

ACCIDENTAL RELEASE MEASURES

Personal Precautions, PPE and Emergency Procedures Spill is flammable (until LPG dissipates). Eliminate all sources of ignition including static discharge. Wear protective gloves and safety glasses to prevent contamination of skin and eyes.
Minor spills: Keep area well ventilated and wipe up.
Major spills:
Isolate spill or leak area for at least 8 m in all directions. Eliminate all sources of ignition within at least 15 m.
Keep upwind and to higher ground (propellant gas is heavier than air and will seek low points, pay special attention to drains and pits- these will likely be explosive environments).

40- Safety Data Sheet

Aerosol Low Irritant Surface Spray

Environmental Precautions	Major fire: Consider initial evacuation for at least 100 m in all directions
	Notify police and fire brigade of the location, material, UN Number, quantity and emergency contact as well as condition and damage observed. Keep leaking containers away from drains, surface and ground water. Ensure leakage does not enter streams, sewers or drinking water supply.
Containment / Clean up Procedures	Eliminate all ignition sources, including static within at least 15 m. All equipment used when handling the product must be earthed.
	If water is available, spray leaking containers to reduce ignition hazard and disperse gas. Isolate area until gas has dispersed. Ventilate area. Avoid release to the environment. Do not empty into drains or natural waterways. Absorb spill with inert absorbent material (e.g. dry sand or earth) for disposal using an approved method or following local regulations.

HANDLING AND STORAGE

Precautions for Safe Handling	Ensure spray nozzle is always directed away from user. Pressurised container: may burst if heated. Do not pierce or burn can after use. Extremely flammable. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Do not spray on an open flame or ignition source. Do not breathe concentrated, vapour, mist or spray. Local exhaust ventilation may be necessary to minimise excessive vapour concentration (as long as they do not introduce risk of ignition), if levels are likely to be high or in a confined space.
Conditions for Safe Storage	Keep out of reach of children. Store in a well-ventilated area, away from damp or corrosive conditions. Protect from sunlight and do not expose to temperatures exceeding 50 °C / 122 °F. Store in accordance with Dangerous Goods Regulations and transport in accordance with the ADG Code for Dangerous Goods Class 2.1

EXPOSURE CONTROLS / PERSONAL PROTECTION

National Exposure Standards	There is no established TLV (Threshold Limit Value) for this product. Avoid exposure – obtain special instructions before use. Butane - TWA (Time-Weighted Average) is 800ppm / 1900mg/m ³ Propane is an asphyxiant
Biological Limit Values	Not available.
Engineering Controls	No smoking. No flames or sources of ignition. Local exhaust ventilation may be necessary to minimise excessive vapour concentration, if levels are likely to be high or in a confined space.
Personal Protective Equipment (PPE)	Personal Protective Equipment is not required under normal conditions of use., When handling bulk quantities, wear protective gloves and safety glasses. Do not exceed exposure limits. .

PHYSICAL AND CHEMICAL PROPERTIES

40- Safety Data Sheet

Aerosol Low Irritant Surface Spray

Appearance	Aerosol, Fine clear spray
Odour	Solvent like
pH	Not available
Vapour Pressure	Not available
Vapour Density	Not available
Boiling point	-42 to 0°C
(propellant)	
Solubility in Water	Immiscible
Specific Gravity	0.58 approx.
(propellant)	
Flash Point (propellant)	-104 to -60°C
Flammable limits	1.5% to 9.6% in air (v/v)
(propellant)	
Ignition Temperature	494°C to 600°C
(propellant)	

STABILITY AND REACTIVITY

Chemical Stability	Stable under normal ambient conditions of storage and use. Avoid heat sources. Aerosol cans may explode/burst violently when subject to extremes of heat or pressure and may become projectiles.
Conditions to avoid	Heat, flames and sparks. Avoid static charge and discharge with high concentrations and in confined space. Avoid damp or corrosive conditions.
Incompatible Materials / Hazardous Reactions	Can react violently with oxidising agents – chlorine, pool chlorine or nitric acid.
Hazardous Decomposition Products	Products may include oxides of carbon and nitrogen.

TOXICOLOGICAL INFORMATION

Potential adverse health effects and symptoms associated with exposure to the material	Vapours may cause light-headedness, drowsiness and dizziness. Ingestion: Unlikely due to high volatility of product, but is harmful, may cause lung damage if swallowed. Eyes: Liquid will cause severe damage. Vapour may cause irritation. Skin: May cause cold burn. Irritating to skin. Inhalation: Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. May cause light-headedness, dizziness and drowsiness. Excessive exposure may cause unconsciousness or even death, due to asphyxiation.
---	---

ECOLOGICAL INFORMATION

The information provided is based on data available for the material and the components of the material.

40- Safety Data Sheet

Aerosol Low Irritant Surface Spray

Ecotoxicity / Persistence / Degradability / Mobility Propellant will vaporise rapidly when released to atmosphere. Propellant consists of hydrocarbons that photo chemically decompose under atmospheric conditions.

DISPOSAL CONSIDERATIONS

Disposal of material must comply with local laws and regulations at time of disposal.

Consumer Instructions Do not pierce or burn can. Containers can be disposed of in the normal household waste stream. Recycle empty can.
Bulk quantities Dispose of according to Local, State and National regulations.

TRANSPORT INFORMATION

Transport in accordance with the requirements of ADG Code.

UN Number 1950
Proper Shipping Name (ADG 7, IMDG) AEROSOLS
Proper Shipping name (IATA) AEROSOLS, FLAMMABLE
EMS Code F-D, S-U
Emergency Procedure Guide 2D1
Class and subsidiary risk(s) 2.1
Packaging Group None allocated
Hazchem Code 2YE
Special Precautions for Users Keep out of reach of children.
Spray in well-ventilated area.
Keep away from sources of ignition – No smoking.
Extremely flammable - Do not spray on a naked flame or any incandescent material.
DO NOT spray directly on humans, pets, exposed food, food preparation areas or food utensils. Remove or cover fish tanks before spraying.
Avoid breathing product spray.

REGULATORY INFORMATION

Poisons Schedule Not applicable
Additional information Not applicable